

Tutorials

Jenkins local

Jenkins PVE

Import into JVM keystore

```
# Import certificate openssl s_client -showcerts -connect https://dvsdnet2.devoteam.de\ < /dev/null  
2> /dev/null | openssl x509 -outform PEM > ~/root_ca.pem
```

```
# Duplicate Java Keystore file and move into Jenkins... mkdir $JENKINS_HOME/keystore/ cp  
$JAVA_HOME/jre/lib/security/cacerts $JENKINS_HOME/keystore/
```

```
# Add Certificate to Keystore keytool -import -alias $ALIAS -keystore  
$JENKINS_HOME/keystore/cacerts -file ~/root_ca.pem
```

```
# Add -Djavax.net.ssl.trustStore=$JENKINS_HOME/keystore/cacerts to the # Jenkins startup  
parameters. For Debian/Ubuntu, this is /etc/default/jenkins echo 'JAVA_ARGS="$JAVA_ARGS -  
Djavax.net.ssl.trustStore=$JENKINS_HOME/keystore/cacerts"'
```

```
|  
| /etc/default/jenkins
```

```
sudo service jenkins restart
```

From:

<https://wiki.netzwissen.de/> - **netzwissen.de Wiki**

Permanent link:

<https://wiki.netzwissen.de/doku.php?id=jenkins&rev=1693326285>

Last update: **17/08/2024 - 07:06**

