

Debugging

Doku: <https://wiki.mozilla.org/MailNews:Logging>

Module:

- imap
- ImapAutoSync
- ldap
- mime
- msgdb (level 1=opens/closes, level 5 lists open db's on close, number of msg hdrs in use)
- nntp
- pop3
- smtp

Loglevel

- PR_LOG_NONE = 0, /* nothing */
- PR_LOG_ALWAYS = 1, /* always printed */
- PR_LOG_ERROR = 2, /* error messages */
- PR_LOG_WARNING = 3, /* warning messages */
- PR_LOG_DEBUG = 4, /* debug messages */
- 5 (recommended)

z. B. für imap und smtp: Umgebungsvariable für beide Module

```
export NSPR_LOG_MODULES=imap:5,smtp:5,timestamp
```

Dann Umgebungsvariable für Logfile

```
export NSPR_LOG_FILE=/tmp/tbmail.log
```

Erscheinungsbild

Doku siehe http://kb.mozillazine.org/Category:Visual_customizations_%28Thunderbird%29 und <https://www.eriwen.com/css/tweaking-thunderbirds-chrome/>

- Verzeichnis Chrome erstellen
- darin userChrome.css erstellen. Formatierungsbeispiele:

```
/* Global UI font */
* { font-size: 11pt !important;
    font-family: Verdana !important;
}
```

Trees individuell

```
#folderTree> treechildren {font-size: 12px; font-family: Arial;}  
#threadTree> treechildren {font-size: 12px; font-family: Arial;}  
#dirTree> treechildren {font-size: 12px; font-family: Arial;}  
#abResultsTree> treechildren {font-size: 12px; font-family: Arial}
```

Menüs

```
/* Menu font */  
menu, menulist, menuitem {  
    font-family: Times New Roman !important;  
    font-size: 12pt !important;  
}
```

Konfigurations-Optionen

http://kb.mozillazine.org/About:config_entries

From:

<https://wiki.netzwissen.de/> - **netzwissen.de Wiki**

Permanent link:

<https://wiki.netzwissen.de/doku.php?id=thunderbird&rev=1486751998>

Last update: **17/08/2024 - 07:06**

